

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.10.2018

Version number 6

Revision: 25.10.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: illbruck OS120

MSDS code: A-I-OS120

1.2 Relevant identified uses of the substance or mixture and uses advised against

Restricted to professional users.

Do not use with flexible PVC due to the risk of plasticiser migration.

Application of the substance / the mixture Sealant

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

tremco illbruck Productie B.V.

Vlietskade 1032, 4241 WC Arkel

T: +31 (0) 183568000, F: +31 (0) 183568100

msds@tremco-illbruck.com

Further information obtainable from:

tremco illbruck Ltd

Coupland Road, Hindley Green, Wigan, WN2 4HT

T: +44 (0) 1942251400, F: +44 (0) 1942251410

www.tremco-illbruck.co.uk, uk.info@tremco-illbruck.com

1.4 Emergency telephone number:

During office hours tel.: +44 (0) 1942251400. At all other times it is recommended to call NHS 111 (England/Wales/Scotland), 01 809 2166 (ROI), or otherwise to contact a doctor.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Repr. 2 H361d Suspected of damaging the unborn child.

STOT SE 3 H336 May cause drowsiness or dizziness.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02 GHS07 GHS08 GHS09

Signal word Danger

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.10.2018

Version number 6

Revision: 25.10.2018

Trade name: illbruck OS120

(Contd. of page 1)

- **Contains:**

toluene
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane
acetone

- **Hazard statements**

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H361d Suspected of damaging the unborn child.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.
H411 Toxic to aquatic life with long lasting effects.

- **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243 Take action to prevent static discharges.
P261 Avoid breathing vapours.
P263 Avoid contact during pregnancy and while nursing.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P314 Get medical advice/attention if you feel unwell.
P403+P235 Store in a well-ventilated place. Keep cool.

- **Supplemental information:**

EUH208 Contains reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700), Bisphenol F epoxy resin. May produce an allergic reaction.
Restricted to professional users.

- **2.3 Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**

- **Description:** Mixture of substances listed below with non-hazardous additions.

- **Dangerous components:**

CAS: 108-88-3 EINECS: 203-625-9 Reg.nr.: 01-2119471310-51-xxxx	toluene Flam. Liq. 2, H225; Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336	10-<20%
EC number: 921-024-6 Reg.nr.: 01-2119475514-35-xxxx	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	5-<10%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2219471330-49-xxxx	acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	1-<5%

(Contd. on page 3)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.10.2018

Version number 6

Revision: 25.10.2018

Trade name: illbruck OS120

(Contd. of page 2)

CAS: 1314-13-2 EINECS: 215-222-5	zinc oxide Aquatic Acute 1, H400; Aquatic Chronic 1, H410	1-<5%
CAS: 25068-38-6 NLP: 500-033-5 Reg.nr.: 01-2119456619-26-xxxx	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700) Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	0.1-<1%
CAS: 119-47-1 EINECS: 204-327-1	6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol Repr. 2, H361f; Aquatic Chronic 4, H413	0.1-<1%
CAS: 9003-36-5 NLP: 500-006-8 Reg.nr.: 01-2119454392-40-xxxx	Bisphenol F epoxy resin Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	0.1-<1%
CAS: 110-54-3 EINECS: 203-777-6	n-hexane Flam. Liq. 2, H225; Repr. 2, H361f; STOT RE 2, H373; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	0.1-<1%

- **SVHC -**

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**

- **General information:**

In case of accident or if you feel unwell, seek medical advice (show this safety data sheet if possible). Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out of danger area and lay down.

Immediately remove any clothing soiled by the product.

- **After inhalation:**

Supply fresh air.

Seek immediate medical advice.

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

Immediately remove all soiled and contaminated clothing

- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

- **After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

- **4.2 Most important symptoms and effects, both acute and delayed**

Headache

Vapours may cause drowsiness and dizziness.

Breathing difficulty

Nausea

May cause an allergic skin reaction.

May cause damage to organs through prolonged or repeated exposure.

Irritating to eyes and skin.

May be fatal if swallowed and enters airways.

- **Information for doctor:** No further relevant information available.

(Contd. on page 4)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.10.2018

Version number 6

Revision: 25.10.2018

Trade name: illbruck OS120

(Contd. of page 3)

- **Hazards** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
Can form explosive gas-air mixtures.
Formation of toxic gases is possible during heating or in case of fire.
Carbon monoxide (CO)
Carbon dioxide (CO₂)
Hydrogen chloride (HCl)
- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.
- **Additional information**
Collect contaminated fire fighting water separately. It must not enter the sewage system.
Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective clothing.
Keep people at a distance and stay on the windward side.
Ensure adequate ventilation.
Keep away from ignition sources.
Avoid contact with the eyes and skin.
- **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Ensure adequate ventilation.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to Section 13.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
Do not breathe vapour.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.10.2018

Version number 6

Revision: 25.10.2018

Trade name: illbruck OS120

(Contd. of page 4)

Avoid contact with the eyes and skin.

Pregnant women should strictly avoid inhalation or skin contact.

Ensure that washing facilities are available at the work place.

Do not eat, drink, smoke or sniff while working.

- **Information about fire - and explosion protection:**

Highly flammable liquid and vapour.

Protect against electrostatic charges.

Fumes can combine with air to form an explosive mixture.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

- **7.2 Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Store only in the original receptacle.

- **Information about storage in one common storage facility:**

Protect from heat and direct sunlight.

Store away from oxidising agents.

- **Further information about storage conditions:**

Store in cool, dry conditions in well sealed receptacles.

Storage temperature: +5°C to +25°C

- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

CAS: 108-88-3 toluene

WEL	Short-term value: 384 mg/m ³ , 100 ppm
	Long-term value: 191 mg/m ³ , 50 ppm
	Sk

CAS: 67-64-1 acetone

WEL	Short-term value: 3620 mg/m ³ , 1500 ppm
	Long-term value: 1210 mg/m ³ , 500 ppm

CAS: 110-54-3 n-hexane

WEL	Long-term value: 72 mg/m ³ , 20 ppm
-----	--

- **DNELs**

- **Long term effects**

CAS: 67-64-1 acetone

Oral	consumer	62 mg/m ³ (general public) (systemic effects)
Dermal	industrial	186 mg/kg/24h (workers) (systemic effects)
	consumer	62 mg/kg/24h (general public) (systemic effects)
Inhalative	industrial	1,210 mg/m ³ (workers) (systemic effects)
	consumer	200 mg/m ³ (general public) (systemic effects)

(Contd. on page 6)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.10.2018

Version number 6

Revision: 25.10.2018

Trade name: illbruck OS120

(Contd. of page 5)

- **Short term effects**

CAS: 67-64-1 acetone

Dermal	industrial	186 mg/m ³ (workers) (systemic effects)
Inhalative	industrial	2,420 mg/m ³ (workers) (local effects)

- **PNECs**

CAS: 67-64-1 acetone

PNEC	100 mg/L (sewage treatment plant)
	10.6 mg/L (sediment (fresh water))
	1.06 mg/L (salt water)
PNEC	29.5 mg/kg (soil)
	3.04 mg/kg (sediment (salt water))
	30.4 mg/kg (sediment (fresh water))

- **Additional information:**

The lists valid during the making were used as basis.

HSE EH40/2005 Workplace Exposure Limits (as amended)

- **8.2 Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Use skin protection cream for skin protection.

Pregnant women should strictly avoid inhalation or skin contact.

- **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Use only in well-ventilated areas.

Take note of emission threshold.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

Filter A2/P3

EN 140

For further guidance,

please refer to HSE HSG53 "Respiratory Protective Equipment at work - A Practical Guide".

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves**

Nitrile rubber, NBR

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.10.2018

Version number 6

Revision: 25.10.2018

Trade name: illbruck OS120

(Contd. of page 6)

EN 374

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

Recommendation:

≥ 8 hours

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

EN 166

- **Body protection:**



Protective work clothing

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Pasty

Colour: Grey

- **Odour:** Characteristic

- **Melting point/freezing point:** Undetermined.

- **Initial boiling point and boiling range:** Undetermined.

- **Flash point:** -1 °C (Closed Cup)

- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

- **Explosion limits:**

Lower: 1.1 Vol %

Upper: 6.7 Vol %

- **Density at 20 °C:** 1.28 g/cm³

- **Solubility in / Miscibility with water:** Insoluble.

- **Viscosity:**

Dynamic at 20 °C: 300,000 - 400,000 cP

- **Solvent content:**

VOC (EU) ≤380 g/l

(Contd. on page 8)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.10.2018

Version number 6

Revision: 25.10.2018

Trade name: illbruck OS120

(Contd. of page 7)

· 9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** Stable
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions**
Reacts with strong acids and alkali.
Reacts with peroxides.
Reacts with oxidising agents.
- **10.4 Conditions to avoid**
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
In case of fire, the following can be released:
Carbon monoxide and carbon dioxide
Hydrogen chloride (HCl)

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:
CAS: 108-88-3 toluene

Oral	LD50	4,328 mg/kg (rat)
Dermal	LD50	6,000 mg/kg (rabbit)
Inhalative	LC50/4 h	21 mg/L (rat)

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

CAS: 67-64-1 acetone

Oral	LD50	5,800 mg/kg (rat) (OECD 401)
Dermal	LD50	20,000 mg/kg (rabbit) (OECD 402)
Inhalative	LC0/4 h	16,000 ppm (rat)
	LC50/4 h	76 mg/L (rat)

CAS: 1314-13-2 zinc oxide

Oral	LD50	>5,000 mg/kg (rat)
------	------	--------------------

CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

Oral	LD50	11,400 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.10.2018

Version number 6

Revision: 25.10.2018

Trade name: illbruck OS120

(Contd. of page 8)

CAS: 110-54-3 n-hexane

Oral	LD50	5,000 mg/kg (mouse)
Dermal	LD50	>2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	172 mg/L (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Strong degreasing effect.
Causes skin irritation.
- **Serious eye damage/irritation** Slight irritation possible.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
Harmful: danger of serious damage to health by prolonged exposure through inhalation.
Chemical pneumonia.
Repeated exposure may cause skin dryness or cracking.
Causes burns.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity**
Suspected of damaging the unborn child.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure**
May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard**
May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:**
Toxic to aquatic life with long lasting effects.

CAS: 108-88-3 toluene

LC50/96 h	24 mg/L (rainbow trout)
	13 mg/L (carassius auratus)
EC50/48 h	11.5 mg/L (daphnia magna)

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

LC50/96 h	1-10 mg/L (fish)
EC50	1-10 mg/L (bacterium)

CAS: 67-64-1 acetone

LC50/96 h	5,540 mg/L (oncorhynchus mykiss)
	7,500 mg/L (leuciscus idus)
EC50/48 h	6,100 mg/L (daphnia magna)
IC50/8 d	7,500 mg/L (scenedesmus quadricauda)

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.10.2018

Version number 6

Revision: 25.10.2018

Trade name: illbruck OS120

(Contd. of page 9)

CAS: 1314-13-2 zinc oxide

LC50/96 h | 1.1 mg/L (fish)

EC50/48 h | >1,000 mg/L (daphnia magna)

CAS: 110-54-3 n-hexane

LC50/24 h | 4 mg/L (carassius auratus)

EC50/48 h | 2.1 mg/L (daphnia magna)

- **12.2 Persistence and degradability** Not easily biodegradable
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

· **Ecotoxic effects:****CAS: 108-88-3 toluene**

IC50/72 h | 12 mg/L (selenstrum capricornutum)

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

IC50/72 h | 10-100 mg/L (algae)

NOEC/21 d | 1-10 mg/L (fish)

CAS: 1314-13-2 zinc oxide

IC50/72 h | 0.1-1 mg/L (algae)

- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
Toxic for aquatic organisms
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Also poisonous for fish and plankton in water bodies.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Disposal must be made according to official regulations.

· **European waste catalogue**

08 04 09* | waste adhesives and sealants containing organic solvents or other hazardous substances

HP 3 | Flammable

HP 4 | Irritant - skin irritation and eye damage

HP 5 | Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

HP 10 | Toxic for reproduction

HP 14 | Ecotoxic

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.10.2018

Version number 6






Revision: 25.10.2018

Trade name: illbruck OS120

(Contd. of page 10)

- **Uncleaned packaging:**
- **Recommendation:**
Dispose of packaging according to regulations on the disposal of packagings.
Packagings that may not be cleansed are to be disposed of in the same manner as the product.
Non contaminated packagings may be recycled.

SECTION 14: Transport information

- | | |
|---|--|
| <ul style="list-style-type: none"> · 14.1 UN-Number · ADR, IMDG, IATA | UN1133 |
| <ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG · IATA | 1133 ADHESIVES, ENVIRONMENTALLY HAZARDOUS
ADHESIVES (HEPTANES), MARINE POLLUTANT ADHESIVES |
| <ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR | <div style="display: flex; align-items: center; gap: 10px;">   </div> <p style="margin-top: 10px;">· Class 3 (F1) Flammable liquids.
· Label 3</p> |
| <ul style="list-style-type: none"> · IMDG | <div style="display: flex; align-items: center; gap: 10px;">   </div> <p style="margin-top: 10px;">· Class 3 Flammable liquids.
· Label 3</p> |
| <ul style="list-style-type: none"> · IATA | <div style="display: flex; align-items: center; gap: 10px;">  </div> <p style="margin-top: 10px;">· Class 3 Flammable liquids.
· Label 3</p> |
| <ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA | III |
| <ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR): | Product contains environmentally hazardous substances: heptane
Yes
Symbol (fish and tree)
Symbol (fish and tree) |

(Contd. on page 12)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.10.2018

Version number 6

Revision: 25.10.2018

Trade name: illbruck OS120

(Contd. of page 11)

<ul style="list-style-type: none"> · 14.6 Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Category 	<p>Warning: Flammable liquids.</p> <p>33</p> <p>F-E,S-D</p> <p>B</p>
<ul style="list-style-type: none"> · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code 	<p>Not applicable.</p>
<ul style="list-style-type: none"> · Transport/Additional information: 	
<ul style="list-style-type: none"> · ADR · Limited quantities (LQ) · Excepted quantities (EQ) 	<p>5L</p> <p>Code: E1</p> <p>Maximum net quantity per inner packaging: 30 ml</p> <p>Maximum net quantity per outer packaging: 1000 ml</p>
<ul style="list-style-type: none"> · Transport category · Tunnel restriction code · Remarks: 	<p>3</p> <p>D/E</p> <p>14.4 : PG III; ADR 2.2.3.1.4</p>
<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) 	<p>5L</p> <p>Code: E2</p> <p>Maximum net quantity per inner packaging: 30 ml</p> <p>Maximum net quantity per outer packaging: 500 ml</p>
<ul style="list-style-type: none"> · Remarks: 	<p>14.4 : PG III; IMDG 2.3.2.2 - 2.3.2.3</p>
<ul style="list-style-type: none"> · IATA · Remarks: 	<p>14.4 : PG III; IATA 3.3.3</p>
<ul style="list-style-type: none"> · UN "Model Regulation": 	<p>UN 1133 ADHESIVES, 3, III, ENVIRONMENTALLY HAZARDOUS</p>

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

"CLP" Regulation (EC) No 1272/2008 (OJ L 353, 31.12.2008, p.1).

"REACH" Regulation (EC) No 1907/2006 (OJ L 396, 30.12.2006, p.1, with subsequent amendments).

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

HSE EH40/2005 Workplace Exposure Limits (as amended)

Guidance on the classification and assessment of waste | Technical Guidance WM3 (1st edition 2015)

2001/118/EC as regards the list of wastes

2008/98/EC on waste

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 40, 48

National regulations:

Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

(Contd. on page 13)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.10.2018

Version number 6

Revision: 25.10.2018

Trade name: illbruck OS120

(Contd. of page 12)

- **Other regulations, limitations and prohibitive regulations**
- **Substances of very high concern (SVHC) according to REACH, Article 57** Not applicable.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H361f Suspected of damaging fertility.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H413 May cause long lasting harmful effects to aquatic life.

- **Department issuing SDS:**

Prepared and verified in accordance with "REACH" Regulation (EC) No 1907/2006, Annex II, Part A, 0.2.3.

- **Abbreviations and acronyms:**

- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- PNEC: Predicted No-Effect Concentration (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- SVHC: Substances of Very High Concern
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids – Category 2
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Skin Sens. 1: Skin sensitisation – Category 1
- Repr. 2: Reproductive toxicity – Category 2
- Repr. 2: Reproductive toxicity – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Asp. Tox. 1: Aspiration hazard – Category 1
- Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
- Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
- Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4

- *** Data compared to the previous version altered.**